

**Rifle:**

**Caliber:** \_\_\_\_\_

\_\_\_\_\_ **Deprime**

\_\_\_\_\_ **Clean in Ultrasonic**

\_\_\_\_\_ **Primer pocket go / no-go**

\_\_\_\_\_ **Swager (if Necessary)**

\_\_\_\_\_ **Anneal (if necessary)**

\_\_\_\_\_ **Lube/Resize**

\_\_\_\_\_ **De-Bur flash hole (if Necessary)**

\_\_\_\_\_ **Trim/Chamfer**

223/5.56 trim to 1.750\*

224 Val trim to 1.590\*\*

300 AAC Blackout 1.358\*\*\*

6.5 Creedmoor 1.190\*\*\*\*

\_\_\_\_\_ **Clean in wet tumbler**

\_\_\_\_\_ **Load**

\* **223 REM** The 2015 standard is 1.760"-0.030", so 1.730"-1.760" is the current range and the middle value is 1.745", which should, by tradition, be the trim-too length.

\*\* **224 VAL** The 2018 standard is 1.600"-0.020", so 1.580"-1.600" is the current range and the middle value is 1.590", which should, by tradition, be the trim-too length.

\*\*\* **300 BLK** The 2015 standard is 1.368"-0.020", so 1.348"-1.368" is the current range and the middle value is 1.358", which should, by tradition, be the trim-too length.

\*\*\*\* **6.5 CREED** The 2015 standard is 1.920"-0.020", so 1.900"-1.920" is the current range and the middle value is 1.910", which should, by tradition, be the trim-too length