

Date:_____

Date:_____

Rifle Caliber: _____

Rifle Caliber: _____

LPP _____ SPP _____

LPP _____ SPP _____

COUNT: _____ ea

COUNT: _____ ea

_____ Deprime

_____ Clean

_____ Primer pocket go / no-go

_____ Swager (if Necessary)

_____ Anneal (if necessary)

_____ Lube/Resize

_____ De-Bur flash hole (if Necessary)

_____ Trim/Chamfer

223/5.56 trim to 1.745*

224 Val trim to 1.590**

300 AAC Blackout 1.358***

6.5 Creedmoor 1.910****

_____ Clean

_____ Load

* **223 REM** The 2015 standard is 1.760"-0.030", so 1.730"-1.760" is the current range and the middle value is 1.745", which should, by tradition, be the trim-too length.

** **224 VAL** The 2018 standard is 1.600"-0.020", so 1.580"-1.600" is the current range and the middle value is 1.590", which should, by tradition, be the trim-too length.

*** **300 BLK** The 2015 standard is 1.368"-0.020", so 1.348"-1.368" is the current range and the middle value is 1.358", which should, by tradition, be the trim-too length.

**** **6.5 CREED** The 2015 standard is 1.920"-0.020", so 1.900"-1.920" is the current range and the middle value is 1.910", which should, by tradition, be the trim-too length